



Adjustable Beam/Lumen Spot Light (SBLABL1)



Description:

- ▶ Powered by second generation Cree CXA series LED
- ▶ Field Adjustable Wattage & Lumen Level provides endless Beam Spread and Brightness design possibilities
- ▶ Set-n-Stake® Quick Link Composite with Brass insert Stake Mount
- ▶ Brass Body and Knuckle with Bronze finish
- ▶ Bayonet Shroud adjustment provides 5 different settings
- ▶ High Impact Glass Lens
- ▶ IP65 Rated for harsh environments
- ▶ 10 Year Warranty
- ▶ Includes Hex Key Adjustment Tool (4mm)
- ▶ Moisture Relief Valves insures No condensation accumulates inside fixture



Features:

- ▶ Beam Angle Adjustment Range from 20° to 60°
- ▶ 2,800°K, 85 CRI, L70 50,000 Hrs. LED
- ▶ 12V - 15V AC/DC Power Range
- ▶ Provided with 6ft 105°C Rated #18/2 Lead Wire
- ▶ Operating range -30°C to +45°C
- ▶ ETL Listed FCC Compliant
- ▶ SBLABL1 Product Covered by Patent #'s: 9,115,857; 9,140,414; 9,316,379; 9,541,263; 9,945,538

SBLABL1 Fixture Electrical and Photometric Test Results. Voltage Range 12V to 15V AC/DC

Testing performed LM79 Standard. Actual field performance can vary by + or - 5%

Power Setting	Voltage Input	Current Input	Consumed Wattage	Power Factor	Volt/ Amp	Light Output at 20° Beam Angle	Light Output at 40° Beam Angle	Light Output at 60° Beam Angle	CCT	CRI
#5, 17 W	12.0 VAC	1.800 A	16.73	0.775	21.6	1,080 lm	1,070 lm	894 lm	2800°K	85
#4, 13 W	12.0 VAC	1.465 A	13.43	0.757	17.7	917 lm	901 lm	757 lm	2800°K	85
#3, 10 W	12.0 VAC	1.122 A	9.9	0.734	13.5	711 lm	697 lm	586 lm	2800°K	85
#2, 7 W	12.0 VAC	0.785 A	6.68	0.71	9.4	494 lm	480 lm	404 lm	2800°K	85
#1, 4 W	12.0 VAC	0.463 A	3.65	0.652	5.6	245 lm	242 lm	208 lm	2800°K	85