CAST **PERIMETER**®

A SERIES
ASTRONOMICAL
AI SERIES
ASTRONOMICAL/INPUT

Maximum Input: 100 - 305 VAC.
Total lamp wattage not to exceed 85% of power supply rating.

Power Supply Model #	Output Voltage	Output Amp (Max)
CPT600DCA (600 WATT)	26VDC	1X20A
CPTI200DCAI (1200 WATT)	26VDC	2X20A
CPTI200DCA (1200 WATT)	26VDC	2X20A

CONFORMS TO ANSI/UL STD 2108
CERTIFIED TO CAN/CSA STD.

C UL US LISTED
LOW VOLTAIGE LUMINAIRE POWER SUPPLY
E519478

PRIMARY AMPERAGE FULL LOAD:

1200 WATT	600 WATT
14.0 AMPS @ 115V	7.0 AMPS @ 115V
6.6 AMPS @ 230V	3.3 AMPS @ 230V
5.8 @ 277V	2.9 AMPS @ 277V

Copyright 2020 CAST LIGHTING LLC
1120-A Goffle Rd., Hawthorne, NJ 07506

:Enclosure Type 3R :Wall Mount Only Mount this unit no less than 1 ft. above ground level.

USE FINE POINT PERMANENT MARKER

POWER SUPPLY NO:

WIRE RUN#	FIXTURE LOCATION	AMPS	CIRCUIT

INPUT POWER PRIMARY WIRING SCHEMATIC. Maximum input 100-305VAC

Installer: NOTE Voltage Used	Voltage	Brown / HOT (USA Black)	Blue / NEUTRAL (USA White)	Green Yellow / GROUND	Notes:
	115V-120V	Brown / HOT	Blue / NEUTRAL	Green Yellow / GROUND	*Wired from Factory
	230V-240V	Brown / HOT	Blue / HOT	Green Yellow / GROUND	Line to Line
	208V	Brown / HOT	Blue / HOT	Green Yellow / GROUND	Line to Line
	277V	Brown / HOT	Blue / NEUTRAL	Green Yellow / GROUND	
	220V (European)	Brown / HOT	Blue / NEUTRAL	Green Yellow / GROUND	

DATE: _____ PRIMARY AMPERAGE READING: _____ PRIMARY VOLTAGE: _____

Not for use with dimmers.

Suitable for Outdoor Use Only.

For Installation in or on non-combustible materials only.

For use with low voltage landscape luminaires and fittings only.

The door must be closed.