


#	Date	Comments

Revisions	

Drawn By: Joe Frey
Checked By:
Date: 12/15/2020
Scale: None

Test Description:
Perimeter Model CPL2
Tested at 17V DC 10' Foot Spacing,
Lumiere 9.5' Feet Off Grade



Green = Values 4:1 Max/Min of Total Calculated Area
Black = Values 4:1 Ave/Min of Total Calculated Area

- Comments:**
- 1) Lux Values Shown are at grade
 - 2) Lux Values shown take into account a 10% reduction in Test data taken at 17V DC
 - 3) Lux Values Grid Spacing is 4 feet

Not to Scale

Symbol	Qty	Label	Arrangement	Lum. Lumens	LLF	Description	Lum. Watts	Arr. Watts	Total Watts
	13	CPL2	SINGLE	529	0.900	CPL2 8w Perimeter	8.194	8.194	106.522

Calculation Summary					
Label	CalcType	Units	Avg	Max	Min
4 to 1 Ave-Min	Illuminance	Lux	4.73	27.28	0.13
4 to 1 Max-Min	Illuminance	Lux	17.01	27.28	6.98

These drawings are for conceptual use only and are not intended for construction. Values represented are an approximation generated from manufacturers photometric inhouse or independent lab tests with data supplied by lamp manufacturers.