



Green = Values 4:1 Max/Min of Total Calculated Area
 Black = Values 4:1 Ave/Min of Total Calculated Area

Cyan = Values > 0, But < 4:1 Ave/Min of Total Calculated Area
 Red = Values = 0

- Comments:
- 1) Lux Values Shown are at grade
 - 2) Lux Values shown take into account a 10% reduction in Test data taken at 17V DC
 - 3) Lux Values Grid Spacing is 4 feet

Not to Scale

Luminaire Schedule									
Symbol	Qty	Label	Arrangement	Lum. Lumens	LLF	Description	Lum. Watts	Arr. Watts	Total Watts
	11	CPL2	SINGLE	529	0.900	CPL2 8w Perimeter	8.194	8.194	90.134

Calculation Summary								
Label	CalcType	Units	Avg	Max	Min	Avg/Min	Max/Min	
4 to 1 Ave-Min_FS16	Illuminance	Lux	3.51	20.15	0.00	N.A.	N.A.	
4 to 1 Max-Min_FS16	Illuminance	Lux	11.16	20.15	4.99	2.24	4.04	

These drawings are for conceptual use only and are not intended for construction. Values represented are an approximation generated from manufacturers photometric inhouse or independent lab tests with data supplied by lamp manufacturers.

Revisions	
#	Date

Comments	

Drawn By: Joe Frey
 Checked By:
 Date: 8/9/2021
 Scale: None

Test Description:
 Perimeter Model CPL2
 Tested at 17V DC 16' Foot Spacing,
 Lumiere 9.5' Feet Off Grade