


#	Date	Comments

Revisions	

Drawn By: Joe Frey
Checked By:
Date: 10/12/2021
Scale: None

Test Description:
Perimeter Model CPL312-180deg
Tested at 17V DC 20' Foot Spacing,
Tilted 15deg Lumiere 10' Feet Off Grade
CL973-3862



Green = Values 4:1 Max/Min of Total Calculated Area
Black = Values 4:1 Ave/Min of Total Calculated Area

Cyan = Values > 0, But < 4:1 Ave/Min of Total Calculated Area
Red = Values = 0

- Comments:**
- 1) Lux Values Shown are at grade
 - 2) Lux Values shown take into account a 10% reduction in Test data taken at 17V DC
 - 3) Lux Values Grid Spacing is 4 feet

All Fixtures include a 15 degree tilt.

Not to Scale

Luminaire Schedule										
Symbol	Qty	Label	Arrangement	Lum. Lumens	LLF	Description	Lum. Watts	Arr. Watts	Total Watts	
⌘	11	CPL312	Single	1820	0.900	CPL312-180	18.3841	18.3841	202.225	

Calculation Summary							
Label	CalcType	Units	Avg	Max	Min	Avg/Min	Max/Min
4 to 1 Ave-Min_CPL312-20	Illuminance	Lux	1.47	23.42	0.00	N.A.	N.A.
4 to 1 Max-Min_CPL312-20	Illuminance	Lux	6.86	23.42	0.37	18.54	63.30
4 to 1 Max-Min_CPL312-20	Illuminance	Lux	13.93	23.42	5.92	2.35	3.96

These drawings are for conceptual use only and are not intended for construction. Values represented are an approximation generated from manufacturers photometric inhouse or independent lab tests with data supplied by lamp manufacturers.