



**Green = Values > 4:1 Max/Min of Total Calculated Area**  
**Black = Values 4:1 Ave/Min of Total Calculated Area**

**Cyan = Values > 0, But < 4:1 Ave/Min of Total Calculated Area**  
**Red = Values = 0**

- Comments:**
- 1) Lux Values Shown are at grade
  - 2) Lux Values shown take into account a 10% reduction in Test data taken at 17V DC
  - 3) Lux Values Grid Spacing is 4 feet

Not to Scale

Luminaire Schedule									
Symbol	Qty	Label	Arrangement	Lum. Lumens	LLF	Description	Lum. Watts	Arr. Watts	Total Watts
CPWP2	7	CPWP2	SINGLE	1383	0.900	CPWP2 Wall Pack 13w	13.26	13.26	92.82

Calculation Summary							
Label	CalcType	Units	Avg	Max	Min	Avg/Min	Max/Min
4 to 1 Ave-Min_X	Illuminance	Lux	0.71	25.74	0.00	N.A.	N.A.
4 to 1 Max-Min_X	Illuminance	Lux	4.73	25.74	0.18	26.28	143.00
4 to 1 Max-Min_X	Illuminance	Lux	13.95	25.74	4.74	2.94	5.43

These drawings are for conceptual use only and are not intended for construction. Values represented are an approximation generated from manufacturers photometric inhouse or independent lab tests with data supplied by lamp manufacturers.



#	Date	Comments

#	Date	Comments

Drawn By: Joe Frey  
 Checked By:  
 Date: 3/10/2023  
 Scale: None

**Test Description:**  
 Perimeter Model CPWP2  
 Tested at 17V DC 20' Foot Spacing,  
 Lumiere 15' Feet Off Grade